Serial No.: 10/694,792

## IN THE CLAIMS:

Please amend claims as follows:

- 1. (canceled)
- 2. (currently amended) A copper-based alloy excellent in dezincing resistance [[comprising]] consisting essentially of, in percentage by weight:

Cu: 57 - 69%,

Sn: 0.3 - 3%

Si: 0.02 - 1.5%,

Bi : 0.5 - 3%, and

Pb: not more than 0.2% (including 0%),

P: 0.02 - 0.2%, and

the balance: Zn and unavoidable impurities,

further containing, in percentage by weight,

at least one of P: 0.02 - 0.2%, Sb: 0.02 - 0.2% and As: 0.02 - 0.2% at a total content of 0.02 - 0.2%,

where the ratio of Si/Sn expressed in weight percentage is in the range of 0.05 - 1 and apparent zinc content as defined by Formula (1) below is in the range of more than 39 - 50 wt.%, and

the balance of unavoidable impurities:

Apparent Zn content =  $[(Zn\% + 2.0 \times Sn\% + 10.0 \times Si\%) / (Cu\% + Zn\% + 2.0 \times Sn\% + 10.0 \times Si\%)] \times 100$  ... (1).

- 3. (canceled).
- 4. (currently amended) A copper-based alloy excellent in dezincing resistance [[comprising]] consisting essentially of, in percentage by weight

Cu: 57 - 69%,

Sn: 0.3 - 3%

Serial No.: 10/694,792

Si: 0.02 - 1.5%,

Bi : 0.5 - 3%,

Pb: not more than 0.2% (including 0%),

P: 0.02 - 0.2%

at least one of P: 0.02 - 0.2%, Sb: 0.02 - 0.2% and As: 0.02 - 0.2% at a total content of 0.02 - 0.2%, and

at least one of Fe : 0.01 - 0.5%, Ni : 0.01 - 0.5%, Mn : 0.01 - 0.5%, Al : 0.01 - 0.5%,

Cr: 0.01 - 0.5%, Be: 0.01 - 0.5%, Zr: 0.01 - 0.5%, Ce: 0.01 - 0.5%, Ag: 0.01 - 0.5%

0.5%, Ti: 0.01 - 0.5%, Mg: 0.01 - 0.5%, Co: 0.01 - 0.5%, Te: 0.01 - 0.2%, Au:

0.01 - 0.5%, Y: 0.01 - 0.5%, La: 0.01 - 0.5%, Cd: 0.01 - 0.2%, Ca: 0.01 - 0.5% and

B: 0.01 - 0.5% at a total content of 0.01 - 3%, and

the balance: Zn and unavoidable impurities,

where the ratio of Si/Sn expressed in weight percentage is in the range of 0.05 – 1 and apparent zinc content as defined by Formula (1) below is in the range of more than 39 – 50 wt.%, and

the balance of unavoidable impurities:

Apparent Zn content =  $[(Zn\% + 2.0 \times Sn\% + 10.0 \times Si\%) / (Cu\% + Zn\% + 2.0 \times Sn\% + 10.0 \times Si\%)] \times 100$  ... (1).

- 5. (canceled)
- 6. (previously presented) A copper-based alloy excellent in dezincing resistance according to claim 2, wherein one or both of Si-system leadless brass scrap and Bi-system leadless brass scrap are used as source starting material for Si and Bi, respectively.
  - 7. (canceled)
- 8. (previously presented) A copper-based alloy excellent in dezincing resistance according to claim 4, wherein one or both of Si-system leadless brass scrap and Bi-

Serial No.: 10/694,792

system leadless brass scrap are used as source starting material for Si and Bi, respectively.